

Zirkonzahn[®]

Human Zirconium Technology



PRETTAU[®] ANTERIOR[®]

WE HAVE LEARNED SOMETHING MORE

PRETTAU® ANTERIOR®

OVERVIEW OF CHARACTERISTICS:

- *New zirconia – same transparency as lithium disilicate*
- *Particularly suited for the anterior tooth region*
- *Bending strength: 670 MPa (School of Dental Medicine, University of Pennsylvania)*
- *For single crowns, inlays, onlays, veneers, max. 3-unit bridges (fully anatomic or reduced)*
- *Fully biocompatible*
- *Sintering temperature: 1,500 °C (2,732 °F)*
- *Blanks available in different heights*
- *Customizable with Colour Liquid Prettau® Anterior® Aquarell, Ceramics ICE Zirkon Keramik as well as Stains ICE Zirkon Malfarben Prettau® and ICE Zirkon Malfarben 3D by Enrico Steger*



Prettau® Anterior® milled

Prettau® Anterior® colored with Color Liquid Prettau®



Prettau® Anterior® sintered and customized with Stains ICE Zirkon Malfarben 3D by Enrico Steger



Prettau® Anterior® Aquarell

Prettau® Anterior® sintered

Zirkonzahn®



The perfect anterior tooth esthetics with Prettau® Anterior®

HUMAN ZIRCONIUM TECHNOLOGY

ZIRKONZAHN Worldwide – Phone +39 0474 066 680 – info@zirkonzahn.com – www.zirkonzahn.com

ZIRKONZAHN USA Inc. – Phone +1 800 989 8931 – Phone +1 678 441 9419 – infousa@zirkonzahn.com



Prettau® Anterior®



Prettau® Zirconia